

## Sheerweave 4500 - 2000mm/2500mm/3200mm



## **Description:**

A 2x2 basketweave 100% polyester screen fabric. Suitable for internal & external use. Available in three widths that can be cut on the cross.

Width: 2000mm, 2500mm, 3200mm (linen, grey, bronze 2500mm only) (ivory 2500mm + 3200mm only).

Suitable for: Roller, Roman & Panel Blinds, Cutting on Cross, Internal & External Use

Colourways: 11 Quality: Screen

## Specification (1SW4):

- Composition: 17% Polyester / 83% Vinyl on Polyester
- Openness Factor: Approximately 5%,
- UV Blockage: Approximately 95%
- Weave: Basketweave
- Fire Classification: Tested to AS 1530 Part II & Part III | BS 5867 Part II, Type B | NFPA 701 TM#1 Small Scale
- Nominal Thickness: 0.61mm
- Nominal Weight: 488 gsm
- · Cutting: Ultrasonic, crush cut

**Solar Optical Properties:** Fabrics installed internally thirty-degree profile angle

Colour	Solar Optical Properties				Shading Coe	Shading Coefficient	
	Ts	Rs	As	Tv	3mm CL	6mm CL	
White	12	74	14	11	0.26	0.27	
White Linen	13	62	25	13	0.35	0.35	
lvory	14	65	21	14	0.33	0.34	
White Grey	10	49	41	11	0.44	0.43	
White Stone	12	61	27	12	0.36	0.36	
Linen (2500mm only)	10	47	43	11	0.45	0.44	
Bronze	8	7	85	10	0.72	0.69	
Charcoal	5	3	92	7	0.74	0.70	
Charcoal Grey	7	10	83	10	0.70	0.67	
Grey (2500mm only)	8	29	63	10	0.57	0.55	
Charcoal Bronze	7	5	88	9	0.73	0.70	

As: Solar Absorptance

Tv: Visual Transmittance

Rs: Solar Reflectance Manufactured: Phifer China

Ts: Solar Transmittance

Care: Fabric should be regularly dusted / vacuumed as appropriate. May be wiped with warm water and mild detergent.

Warranty: 10 years interior use / 5 years exterior use



3mm CL: 3mm Clear Glass

6mm CL: 6mm Clear Glass





Colour Range \*

Microban® antimicrobial protection inhibits the growth of damaging bacte















Sheerweave 4500

bronze

charcoal





charcoal bronze