

**better outward
visibility**

SOLTIS[®] 86

Soltis[®] 86- Eliminating up to 86% of the sun's rays, Soltis[®] 86 is a compromise between necessary solar protection and the need for more light and external visibility. Especially appreciated when applied to homes or buildings with beautiful views.

Weight per m²	300gr
Thickness	0.43mm
Flame retardant	BS 7837



SOLTIS® 86

WIDTH: 177 cm

WEIGHT: 380 g/sqm



FACADE BLINDS



GLASSROOF BLINDS



VERANDA BLINDS

G U A R A N T E E S A N D L A B E L S



ADVANTAGES

- FERRARI PRÉCONTRAINTE® TECHNOLOGY
- TEAR STRENGTH WITHOUT ANY ADDITIONAL REINFORCEMENT
- LOW SPACE REQUIREMENT
- NO BAGGING OR SAGGING
- WEATHER- AND DIRT- RESISTANT
- A SUN PROTECTION ALLOWING MORE LIGHT TRANSMISSION
- NEW METALLIZED FINISHES AND COORDINATED RANGE WITH SOLTIS® 92
- 23 COLOURS: PLEASE CONSULT OUR COLOUR SAMPLE CHART

COLOURS AND REFERENCES (COLOURS GIVEN FOR INDICATION)



Ref. 86-2045

	Ref. 86-2001		Ref. 86-2040
	Ref. 86-2002		Ref. 86-2042
	Ref. 86-2003		Ref. 86-2043
	Ref. 86-2006		Ref. 86-2044
	Ref. 86-2011		Ref. 86-2046
	Ref. 86-2012		Ref. 86-2047
	Ref. 86-2022		Ref. 86-2048
	Ref. 86-2024		Ref. 86-2053
	Ref. 86-2027		Ref. 86-2069
	Ref. 86-2030		Ref. 86-2077
	Ref. 86-2035		Ref. 86-2078

TECHNICAL CHARACTERISTICS

TECHNICAL CHARACTERISTICS	SOLTIS® 86	
WEIGHT	380 g/sqm	EN ISO 2286-2
THICKNESS	0.43 mm	
WIDTH	177 cm	
TENSILE STRENGTH (WARP/WEFT)	230/160 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	45/20 daN/5 cm	DIN 53.363
FLAME RETARDANCY	M1/NFP 92.503 - B1/DIN 4102 - BS 7837 M1/UNE 23727-90- ONORM B 3800 - CLASS 1/CSE 3/77 SN 198 898 - NFPA 701 - T19 - ASTM E 84-95 - AS 1530	
QUALITY MANAGEMENT SYSTEM	ISO 9000	

The technical characteristics shown are average values given as a guide and may be modified.

FERRARI

